

15KV PORTABLE MV ASSEMBLIES

AVAILABLE OPTIONS

- Heat Shrink Logo ID
- Custom lengths
- Lug and Deadbreak Terminations



600A DEADBREAK



CS LUG



15KV PORTABLE MV ASSEMBLIES

Part Number	AWG	Termination A	Termination B	Description
SH15KV40BXXXACSCS	4/0	2 Hole CU Lug (CS)	2 Hole CU Lug (CS)	4/0 Type SH 15kV with Lugs on Both Terminations
SH15KV40BXXXACSDE	4/0	2 Hole CU Lug (CS)	600A Deadbreak	4/0 Type SH 15kV with Lug and Deadbreak
SH15KV40BXXXADEDE	4/0	600A Deadbreak	600A Deadbreak	4/0 Type SH 15kV Deadbreak on Both Terminations

Note: XXX in part number equals desired length: 025, 050, 075, 100, 200, 300

Termination Options Available: **Lug, 600A Deadbreak**

TYPE SH 15KV CABLE

Part Number	Power Conductor Size	Conductor Stranding	Nominal Insulation Thickness	Nominal Jacket Thickness	Approx. O.D.	Approx. Weight		Ampacity 40°C Ambient Temp.
	AWG/MCM		in.	in.		in.	lbs./1000 ft.	kgs/km
4/0SH-15KV	4/0AWG-1	532x0.0197	0.210	0.170	1.453	1570	2337	397