

Edison Extensions/5-15 Straight Blade Extensions

Options

- Custom lengths
- Custom cable identification

genEnergy™



Used for supplying lighter-duty, general-purpose electrical devices in stage and theater productions, studio and event lighting, and in many other entertainment and industrial applications

- Built to **NEMA standards**
- Indoor and outdoor **UL listing/CSA certified**
- **MSHA approved**
- **Factory-tested**
- **Oil, water, abrasion, and UV resistant** outer jacket and insulation
- **Edison plug and connectors**
- **3-wire 15A assemblies**

STRAIGHT BLADE/EDISON EXTENSIONS

Part Number	Rating	Cable	NEMA
P123BJXXXL515	15A, 125 VAC	12/3 SJOOW	5-15 straight blade
P123BXXXE515	15A, 125 VAC	12/3 SOOW	5-15 straight blade

SJOOW 300V CABLE

Part Number	AWG	No. of Conductors	Stranding/ Diameter	Nominal Insulation Thickness		Nominal Jacket Thickness		Nominal O.D.		Approx. Weight lbs./1000 ft.	Ampacity* 30°C Ambient Temp.
				in.	mm	in.	mm	in.	mm		A
SJOOW12-3	12	3	65/30	0.030	0.76	0.045	1.14	0.43	10.9	131	25.0

*Ampacity – Free air measured; based on continuous duty at 90°C conductor temperature

SOOW 600V CABLE

Part Number	AWG	No. of Conductors	Stranding/ Diameter	Nominal Insulation Thickness		Nominal Jacket Thickness		Nominal O.D.		Approx. Weight lbs./1000 ft.	Ampacity* 30°C Ambient Temp.
				in.	mm	in.	mm	in.	mm		A
SOOW12-3	12	3	65/30	0.045	1.14	0.095	2.41	0.59	15.2	217	25.0

*Ampacity – Free air measured; based on continuous duty at 90°C conductor temperature

GENERGY HEADQUARTERS

P.O. BOX 10731
LANCASTER, PA 17605

WAREHOUSES

Houston, TX
Jacksonville, FL
New Holland, PA
Las Vegas, NV

GENERGYPOWERUSA.COM

Phone 717-584-0375
Fax 717-704-8445
Toll-Free 800-308-1330

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

MADE IN USA