

# 5-BANDED CAM LOCK CABLE EXTENSIONS

## Options

- Reversed ground 5-wire sets
- Carrying straps
- Custom lengths
- Custom cable identification

genEnergy™



Assembled with UL and c(UL) Listed SC cable made from annealed no. 30 gauge bare copper stranding

- Banded every 24" with heavy-duty glued shrink
- Durable CPE insulation
- Meets/exceeds flame test requirements of UL and c(UL)
- Resistant to sunlight, water, ozone, abrasion, acids, heat, flame, and chemicals
- Excellent flexibility and durability
- Standard lengths: 25' and 50'

## 5-BANDED CABLE ASSEMBLIES

Male Connector	Female Connector	Length	Description	Part Number
(5) 16 Series Cams	(5) 16 Series Cams	25', 50'	SC	S02BXXXBANDMFC
(5) 16 Series Cams	Bare	25', 50'	SC	S02BXXXBANDMB
Bare	(5) 16 Series Cams	25', 50'	SC	S02BXXXBANDFB

Note: XXX in part number equals desired length: 025, 050

## SC CABLE

Power Conductor Size	Power Conductor Stranding	Nominal Jacket Thickness		Nominal O.D.		Approx. Weight		Ampacity*
		in.	mm	in.	mm	lbs./1000 ft.	kgs/km	
6 AWG	258/30	0.095	2.41	0.371	9.4	131	195	105
4 AWG	410/30	0.095	2.41	0.430	10.9	189	282	140
2 AWG	649/30	0.106	2.69	0.509	12.9	285	424	190
1 AWG	815/30	0.136	3.45	0.611	15.5	379	564	220
1/0 AWG	1032/30	0.136	3.45	0.672	17.1	463	689	260
2/0 AWG	1287/30	0.136	3.45	0.697	17.1	549	816	300
3/0 AWG	1622/30	0.136	3.45	0.777	19.7	674	1003	350
4/0 AWG	2052/30	0.136	3.45	0.803	20.4	814	1212	405

\*Ampacities are based on single conductor in free air, 30°C ambient air temperature 90°C conductor operating temperature per Table 400-5 (B) of the 2008 NEC

GENERGY HEADQUARTERS  
P.O. BOX 10731  
LANCASTER, PA 17605

WAREHOUSES  
Houston, TX  
Jacksonville, FL  
New Holland, PA  
Las Vegas, NV

GENERGYPOWERUSA.COM  
Phone 717-584-0375  
Fax 717-704-8445  
Toll-Free 800-308-1330

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

MADE IN USA