



## STANDARD FEATURES



- cETus listed for use in U.S. and Canada
- UL943-5th Edition Self-Testing GFCI Module with NEMA 4x Test/Resent Buttons
- UL1640 – Open Neutral Protection
- Heavy Duty Powder Coated Enclosure and Legs to Ensure Rugged Jobsite Performance
- Heavy Duty Legs are Oriented in “sled” Fashion for Easy Jobsite Repositioning
- Outdoor Units Provide NEMA 3R Weather Resistance Protection for Circuitry



5-20R



L6-30R



Plug  
Non-NEMA  
50A 125/250V  
CA Standard



Receptacle  
Non-NEMA  
50A 125/250V  
CA Standard

PART NUMBER	RATING	INPUT & FEEDTHRU	OUTPUT
1066FS-3	50A 120/240V	50A 125/250V CS Style	(6) 5-20 Duplexes (3) GFCI Modules (1) L6-30 Receptacle (1) 2P 30A CB



**INDUSTRY EXCLUSIVE  
UL943-5TH EDITION  
SELF-TESTING GFCI**



**30A 250V, GFCI  
PROTECTED LOCKING  
RECEPTACLE**



**DOUBLE COVER  
DUPLEX RECEPTACLE  
WEATHER RESISTANT COVERS**